

Thermal Carafe Coffee Brewer Pourover and Automatic



Model CDBC15-TC
 (no warmers) (thermal carafe sold separately)
 Dimensions: 17.9" H x 9" W x 18.5" D
 (45.5cm H x 22.9cm W x 55.4cm D)

Features

12 Cup Automatic Coffee Brewer

- Brews 3.9 to 6.8 gallons (14.78 to 25.77 liters) of perfect coffee per hour.
- Accepts thermal carafe up to 8.5" tall (21.6cm).
- Use in quick turn environment where high quality coffee is continuously refreshed.
- Models are space saving 9.0" wide (22.9cm).
- All stainless steel construction.
- Hot water faucet available on automatics
- SplashGard® funnel deflects hot liquids away from the hand.
- Automatically adjusts to varying water pressure.
- Quicker install with pot level, cold brew lock-out and tank temperature set using the simple-to-program touch pad controls.
- Faster service by use of feedback information from built-in electronic diagnostics.

For current specification sheets and other information, go to www.bunn.com.

* International models may vary in appearance.

Related Products

Easy Clear® EQ-17-TL
 Product No. : 30200.1000
 Dimensions:
 12⁷/₁₆" H x 2¹/₂" W x 3" D
 31.6 cm H x 6.35 cm W x 7.62 cm D



Thermal Carafe
 Product No. : 18022.6002
 Capacity 1.9 liter (64 oz)
 Dimensions: 8"H x 6.4"W x 8.2"D
 (20.3cm H x 16.3cm W x 21cm D)



Paper Filter Pack
 Product No. : 20115.6000
 Packed per case: 1,000
 Dimensions: 4¹/₄" Base x 2³/₄" Sidewall
 10.8 cm Base x 6.98 cm Sidewall



Model

Agency Listing

CDBC15-TC



Dimensions & Specifications



Model	Product #	Volts	Amps	Tank Htr Watts	Total Watts	Capacity per hour	Cubic ft ³ /m ³	Weight lbs/kg	Cord Attached
CDBCF15-TC*	29000.6012	120	12.5	1450	1500	4.2 gal/15.92 liter	5.1/.144	31 / 14.1	Yes**
CDBCF35-TC*	29000.6015	120/240	14.6	3500	3500	6.8 gal/25.77 liter	5.1/.144	29 / 13.2	No

* Includes a stainless steel funnel **Power cord (NEMA 5-15P) 15 Amp-120V machine only.

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Requires 2-wires plus ground service rated 120V single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.

CDBCF15-TC

